

IECHO — CORTADORA DIGITAL DE ETIQUETAS

IECHO RK2

Procesa materiales autoadhesivos integrando laminado, corte, ranurado, bobinado y descarga de residuo; velocidad por cabezal de hasta 15 m/min y control multicabezal. Modelos: RK2.



CARACTERÍSTICAS PRINCIPALES

- No need for dies
- Multiple cutting heads are intelligently controlled.
- Efficient cutting
- The maximum cutting speed of single head is 15m/min, and the cutting efficiency of four heads can reach 4 times.
- Slitting
- With the addition of a slitting knife, the slitting can be realized.
- Lamination
- Supports cold lamination, which is performed at the same time as cutting.

APLICACIONES

Post-impresión de etiquetas publicitarias..

ESPECIFICACIONES TÉCNICAS

Especificaciones técnicas (fabricante)

Tipo	RK2-330
Material support width	60-320mm
Maximum cut label width	320mm
Cutting tag length range	20-900mm
Die cutting speed	15m/min(specifically / it is according to die track)
Number of cutting heads	4
Number of split knives	Standard 5(selected / according to demand)
Die cutting method	Imported alloy die cutter
Tipo de máquina	RK
Diámetro máx. de rollo	400mm
Longitud máx. de rollo	380mm
Roll core diameter	76mm/3inc

Largo máx. de etiqueta	440mm
Ancho máx. de etiqueta	380mm
Min slitting width	12mm
slitting quantity	4 standard (optional more)
Rewind quantity	3 rolls (2 rewinding 1 waste removal)
Posicionamiento	CCD
Cutter head	4
Precisión de corte	±0.1 mm

Información publicada por el fabricante (Hangzhou IECHO). Solicite la ficha completa del modelo y configuración para su aplicación.